

ULTRAMATTE™

SPECIALTY THERMAL OVERLAMINATE FILM

LuxeFilms® UltraMatte™ is a scuff-resistant laminating film provides a significantly higher resistance to scuffing and scratching over standard matte films, while providing a soft tactile feel for consumer engagement.

LuxeFilms® UltraMatte™ laminating film allows for the bonding of spot UV coating, glues, and foil stamping with ease.

KEY BENEFITS

- Scuff and Burnish Resistant
- Reduces Spoilage
- Highly Cost Competitive
- Extreme Surface Hardness
- Accepts Spot UV; Glueable and Stampable
- Total Satisfaction Gold Seal Guarantee™

SUGGESTED USES

- High Use Pocket Folders
- Promotional Pieces
- Business Cards
- Soft and Hardbound Book Covers
- Cosmetic and Jewelry Packaging
- Electronics Packaging
- Three Ring and Media/Binders and Cases
- Liquor and Luxury Product Packaging
- High Use Folding Carton Packaging
- Rigid Boxes

Properties	Side	Value	Units	Test Method / Standard
Thickness		1.2	Mil	DIN EN ISO 534
		30	Microns	
Substance/Grammage		23.18	g/m ²	ISO 536
Yield		46.08	m ² /kg	DIN 53375
Haze		91.6	%	ASTM D1003
Gloss		1.5	GU	ASTM D2457
Dyne Level		46	Dyne	DIN 55660-2
Application Temperature		212-248°F (100-120°C)	°F (°C)	Various Equipment- Always Test
Lamination Tensile Strength	MD	58.4	N/mm ²	ASTM D882
	TD	123.7	N/mm ²	
Elongation at Break	MD	186	%	ASTM D882
	TD	98	%	

A = Adhesive Side B = BOPP Side MD = Main Direction TD = Transverse Direction

Note: The information given on this specification sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Nobelus™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.



Enhancing People, Partners
and the World's Brands